

MVRPC CY 2019 Resurfacing Program (ADA Compliance)

Documentation of ADA compliance by field evaluation is required. The *ODOT ADA Rights of Way Inventory Manual* (below) may assist in the field evaluation.

A local jurisdiction should submit a statement with their application indicating that a field visit took place (date of visit), measurements were taken, and ADA compliance of ramps within the project verified. Submitting documentation to MVRPC or ODOT is not required but should be kept in case compliance is ever questioned.




ODOT ADA RIGHTS OF WAY INVENTORY MANUAL

https://www.mvrpc.org/sites/default/files/final_odot_ada_rights_of_way_inventory_manual.pdf

Examples

Perpendicular Curb Ramp Characteristics	
RAMP TYPE	Perpendicular
RAMP SLOPE	8.33% max. (12:1)
RAMP CROSS SLOPE	2% max. (50:1)
RAMP WIDTH	4' min.
LANDING LENGTH	4' min.
LANDING WIDTH	4' min.
LANDING CROSS SLOPE	2% max. (50:1)
FLARE SLOPE LEFT (%):	N/A
FLARE SLOPE RIGHT (%):	N/A



Perpendicular curb ramps shall have a running slope that cuts through or is built up to the curb at right angles or meetings the gutter grade break at right angles (R302.2.1, 2011 Proposed Accessibility Guidelines for Pedestrian Facilities in the Public Rights-of-Way)

Perpendicular curb ramps can require a lot of space to accommodate the ramp and level landing.

